

Model	Max. Power (hp)	Max. Power (kw)	Reversible	Torque Stall (ft-lb)	Torque Stall (Nm)	Free Speed (rpm)	Torque Output @ Max. H.P. (ft-lb)	Torque Output @ Max. H.P. (Nm)	Speed at Max. Power (rpm)	Starting Torque (ft-lb)
4800D	3.8	2.83	No	7.7	10.4	9850	3.85	5.22	4925	5.8
4800K	3.7	2.76	No	47	63.7	1538	23.5	31.86	769	35.3
4800M	3.7	2.76	No	69	93.6	1050	34.5	46.78	525	51
4800N	3.7	2.76	No	100	136	726	50	67.79	363	75
4800P	3.5	2.61	No	131	178	510	65.5	88.81	255	98
4800Q	3.5	2.61	No	173	235	375	86.5	117.29	187.5	129
4800S	3.5	2.61	No	238	323	275	119	161.34	137.5	178
4800U	3.5	2.61	No	354	480	185	177	239.98	92.5	265
4840D	3.3	2.46	Yes	6.9	9.4	9100	3.45	4.68	4550	5.2
4840K	3.2	2.39	Yes	42.7	57.9	1429	21.35	28.95	714.5	32
4840M	3.2	2.39	Yes	63	85.4	975	31.5	42.71	487.5	47.3
4840N	3.2	2.39	Yes	90.2	122	675	45.1	61.15	337.5	67.7
4840P	3	2.24	Yes	125	170	475	62.5	84.74	237.5	93
4840Q	3	2.24	Yes	165	224	350	82.5	111.85	175	123
4840S	3	2.24	Yes	215	292	255	107.5	145.75	127.5	162
4840U	3	2.24	Yes	300	407	170	150	203.37	85	225