

Model	Max. Power (hp)	Max. Power (kw)	Reversible	Torque Stall (ft-lb)	Torque Stall (Nm)	Free Speed (rpm)	Torque Output @ Max. H.P. (ft-lb)	Torque Output @ Max. H.P. (Nm)	Speed at Max. Power (rpm)	Spindle
7533-B	0.25	0.19	No	8.2	11.1	550	4.1	5.4	275	3/8 in. -24 Threaded
7534-B	0.25	0.19	No	5	6.7	900	2.5	3.2	450	3/8 in. -24 Threaded
7535-C	0.25	0.19	No	1.75	2.3	2700	0.875	1.1	1350	3/8 in. -24 Threaded
7536-B	0.25	0.19	No	1.05	1.4	4500	0.525	0.66	2250	3/8 in. -24 Threaded
7537-C	0.25	0.19	No	0.22	0.3	20000	0.11	14	10000	3/8 in. -24 Threaded
7538-B	0.25	0.19	No	8.2	11.1	550	4.1	5.4	275	3/8 in. Keyed
7539-B	0.25	0.19	No	5	6.7	900	2.5	3.2	450	3/8 in. Keyed
7540-B	0.25	0.19	No	1.75	2.3	2700	0.875	1.1	1350	3/8 in. Keyed